

Summit Pro Series

TOPCon Bifacial
132 - cell Module

TW-720HT

700-720W

0-3%Positive Tolerance



Monocrystalline




Half Cell



18BB



Grade A



• MODULE FEATURES



High efficiency

TOPCon technology improves efficiency, increases power generation, and contributes to lower LCOE.



Lower heat spot risk

Innovative circuit design and “Half Cell” structure decrease the temperature of heat spots and effectively reduce power loss.



Excellent low-light performance

Reliable performance in low-light conditions such as in the morning, at dusk or during raining days.



Resilient to extreme weather

Carefully selected materials ensure the module still works well under the condition of 2400Pa wind load and 5400Pa snow load.



PID resistant

High quality solar cell and advanced processing technology contribute to excellent PID resistance performance.



Double-sided electricity generation

Power can be generated on both sides to support additional output gains of up to 25%. The multi-busbar half-cut technology can boost energy density to deliver higher output.


• Quality Certification



• Product Qualification



• Performance Warranty



15 15 Years Product Warranty

30 30 Years Linear Power Warranty

TW-720HT

•Product Specification•

Cell Type	Mono crystalline
Cell Quantity	132 cell
Cell Size (mm)	210*105
Module Size (mm)	2384*1303*33
Module Weight (kg)	37.9
Glass Thickness (mm)	2.0
Frame Material	Anodized aluminum alloy
Junction Box	IP68
Cable/Connector	4mm ² , MC4compatible
Cable Length	+300mm/-300mm; or Customize
Max System Volt (V)	1500V DC
Max Fuse Rate (A)	35
Power Tolerance	0~+3%

•Electrical Characteristics•

STC standard performance >>>

Power Level	700	705	710	715	720
Pmax(W)	700	705	710	715	720
Vmp(V)	40.35	40.52	40.69	40.86	41.03
Imp(A)	17.35	17.40	17.45	17.50	17.55
Voc(V)	48.60	48.77	48.94	49.11	49.28
Isc(A)	18.35	18.40	18.45	18.50	18.55
Module Efficiency(%)	22.53	22.70	22.90	23.01	23.18

NOCT standard performance >>>

Power Level	700	705	710	715	720
Pmax(W)	526	530	534	538	541
Vmp(V)	37.55	37.73	37.90	38.08	38.18
Imp(A)	14.01	14.05	14.09	14.13	14.17
Voc(V)	46.17	46.33	46.49	46.65	46.82
Isc(A)	14.82	14.86	14.90	14.94	14.98


•Bifacial output-backside power gain•

5%Pmax(W)	735	740	746	750	756
5% Module Efficiency	23.66	23.83	24.00	24.17	24.34
15% Pmax(W)	805	811	817	822	828
15% Module Efficiency	25.91	26.10	26.28	26.47	26.66
25% Pmax(W)	875	881	888	894	900
25% Module Efficiency	28.17	28.37	28.57	28.77	28.97



•Temperature Characteristics•

Operating Temp (°C)	-40~85
Operating Humidity (%)	5~85
Hail Load Tolerance	25mm hailstone with velocity of 23m/s
Temp Coefficient (%) / °C	-0.28
Temp Coefficient Isc (%) / °C	-0.24
Temp Coefficient Voc (%) / °C	0.046
Operating Temp (°C)	44±2

•Engineering Drawings•



•I-V Curve•



•Packaging Info•

Pieces per Pallet	34
Size of Packaging (mm)	1325*1130*2510
Weight of per Pallet (kg)	1317
Pieces per Container	612
Size of Container	40'HC



Add: Shangman Industrial Park, Caobu Town
Rudong County, Nantong City, Jiangsu Province, China
Tel: 86-513-69976081/81900128
Web: www.techwisesolar.com
Email: salesdept@techwisesolar.com

All data and specifications included in this brochure
may subject to be modified without notice.
All Rights reserved by TechWise Solar Co.
(Mar 2024 V3 Edition)